

# Lecture-3

## Two Basic Bootstrap Pages-

- 1- The following example shows the code for a basic Bootstrap page (with a responsive fixed width container):

### Example-

```
<!DOCTYPE html>

<html lang="en">

<head>

  <title>Bootstrap Example</title>

  <meta charset="utf-8">

  <meta name="viewport" content="width=device-width, initial-scale=1">

  <link rel="stylesheet"
href="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.7/css/bootstrap.
min.css">

  <script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.2.1/jquery.min.js"><
/script>

  <script
src="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.7/js/bootstrap.mi
n.js"></script>
```

```
</head>

<body>

<div class="container">

  <h1>My First Bootstrap Page</h1>

  <p>This part is inside a .container class.</p>

  <p>The .container class provides a responsive fixed width container.</p>

</div>

</body>

</html>
```

- 2- The following example shows the code for a basic Bootstrap page (with a full width container):

## Example-

```
<!DOCTYPE html>
<html lang="en">
<head>
  <title>Bootstrap Example</title>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-
scale=1">
```

```
<link rel="stylesheet"
href="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.7/css/bootstr
ap.min.css">
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.2.1/jquery.min.j
s"></script>
<script
src="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.7/js/bootstrap
.min.js"></script>
</head>
<body>

<div class="container-fluid">
  <h1>My First Bootstrap Page</h1>
  <p>This part is inside a .container-fluid class.</p>
  <p>The .container-fluid class provides a full width container,
spanning the entire width of the viewport.</p>
</div>

</body>
</html>
```